


MAS BT



Gewuchtet G = 6,3 15.000 U/min.
Vyvážení G = 6,3 15 000 U/min.

Fräseraufnahme MAS BT für Einschraubfräser
Držáky pro šroubovací frézy MAS BT

Größe / Rozměr	G	D2 mm	D1 mm	D mm	A mm	L mm	Art.-Nr. / Obj. č.	EUR
BT 40	M8	8,5	13	23	77	50	13-FABT40-M8-50	62,00
BT 40	M8	8,5	13	25	120	100	13-FABT40-M8-100	72,40
BT 40	M10	10,5	18	20	52	25	13-FABT40-M10-25	62,00
BT 40	M10	10,5	18	23	77	50	13-FABT40-M10-50	62,00
BT 40	M10	10,5	18	28	102	75	13-FABT40-M10-75	62,00
BT 40	M10	10,5	18	32	127	100	13-FABT40-M10-100	72,40
BT 40	M12	12,5	21	24	52	25	13-FABT40-M12-25	62,00
BT 40	M12	12,5	21	28	77	50	13-FABT40-M12-50	62,00
BT 40	M12	12,5	21	31	102	75	13-FABT40-M12-75	62,00
BT 40	M12	12,5	21	31	138	100	13-FABT40-M12-100	72,40
BT 40	M16	17	29	29	52	25	13-FABT40-M16-25	66,20
BT 40	M16	17	29	34	77	50	13-FABT40-M16-50	66,20
BT 40	M16	17	29	34	102	75	13-FABT40-M16-75	66,20
BT 40	M16	17	29	41	138	100	13-FABT40-M16-100	77,60
BT 40	M16	17	29	44	152	125	13-FABT40-M16-125	86,90
BT 40	M16	17	29	50	188	150	13-FABT40-M16-150	98,30
BT 50	M8	8,5	13	23	88	50	13-FABT50-M8-50	110,70
BT 50	M8	8,5	13	25	138	100	13-FABT50-M8-100	115,70
BT 50	M8	8,5	13	30	188	150	13-FABT50-M8-150	125,60
BT 50	M10	10,5	18	23	88	50	13-FABT50-M10-50	110,70
BT 50	M10	10,5	18	32	138	100	13-FABT50-M10-100	115,70
BT 50	M10	10,5	18	37	188	150	13-FABT50-M10-150	121,50
BT 50	M12	12,5	21	24	88	50	13-FABT50-M12-50	110,70
BT 50	M12	12,5	21	33	138	100	13-FABT50-M12-100	107,10
BT 50	M12	12,5	21	40	188	150	13-FABT50-M12-150	115,70
BT 50	M16	17	29	34	88	50	13-FABT50-M16-50	110,70
BT 50	M16	17	29	36	138	100	13-FABT50-M16-100	126,50
BT 50	M16	17	29	43	188	150	13-FABT50-M16-150	141,30

