



Anzugsbolzen Upínací čepy



S 20x2, mit Sägewinde S 20x2, s pilovým závitem


Größe / Rozměr	G	G1	D1 mm	D3 mm	L1 mm	Art.-Nr. / Obj. č.	EUR
SK 40	M 16	S 20x2	16,6	17	58	13-9886B-40-58	12,70

MAS BT, 45° MAS BT, 45°




Größe / Rozměr	G	D1 mm	D2 mm	D3 mm	L1 mm	L2 mm	Art.-Nr. / Obj. č.	EUR
SK 30	M 12	11	7	13	43	24	13-9882B-30-45	7,40
SK 40	M 16	15	10	17	60	35	13-9882B-40-45	5,70
SK 50	M 24	23	17	25	85	45	13-9882B-50-45	8,60

MAS BT, 60° MAS BT, 60°




Größe / Rozměr	G	D1 mm	D2 mm	D3 mm	L1 mm	L2 mm	Art.-Nr. / Obj. č.	EUR
SK 30	M 12	11	7	13	43	24	13-9882B-30-60	9,40
SK 40	M 16	15	10	17	60	35	13-9882B-40-60	5,70
SK 50	M 24	23	17	25	85	45	13-9882B-50-60	8,60

MAS BT, 90° MAS BT, 90°



Größe / Rozměr	G	D1 mm	D2 mm	D3 mm	L1 mm	L2 mm	Art.-Nr. / Obj. č.	EUR
SK 40	M 16	15	10	17	60	35	13-9882B-40-90	5,70
SK 50	M 24	23	17	25	85	45	13-9882B-50-90	8,60

MAS BT, 45°, mit Bohrung MAS BT, 45°, s otvorem



Größe / Rozměr	G	D1 mm	D2 mm	D3 mm	D4 mm	L1 mm	L2 mm	Art.-Nr. / Obj. č.	EUR
SK 40	M 16	15	10	17	7	60	35	13-9882A-40-45	5,70
SK 50	M 24	23	17	25	11,5	85	45	13-9882A-50-45	8,60